

## WRX TRADE EGGSHELL INTERIOR PAINT Product Data Sheet

---

**Product Number:** 03.600

**Issued:** 04/2022

**Revision:** 00

---

### DESCRIPTION

Top quality, water-based, easy to clean, interior top-coat paint based on pure acrylic emulsion offering an eggshell finish.

### USAGE AREA

Suitable for use on standard interior surfaces.

### PROPERTIES

Its unique formula, with Stain Repellent Technology, lives up to the challenges of everyday life. The durable surface allows marks and home stains to be easily wiped away. It gives a tough film with high scrub resistance (Class 1 for ISO 11998) and protects surfaces. It provides excellent coverage with a high-quality finish.

### PRODUCT INFORMATION

**Finish:** Eggshell

**Colour Range:** Card colours

**Composition:** Solvent: Water

Binder: Acrylic polymer

Pigment: Titanium dioxide, coloured pigments, extenders.

**Volume Solids:** 40%, white. Other colours will vary.

**Coverage:** WRX Trade Eggshell Interior Paint will cover up to 18 m<sup>2</sup> per litre, depending on the surface conditions.

**Wet Film Thickness:** 56 micrometres at 18 m<sup>2</sup> per litre

**Dry Film Thickness:** 22 micrometres at 18 m<sup>2</sup> per litre

**Drying Time:** Touch dry in half an hour under normal conditions. Allow 6 hours between coats.

**VOC Content:** VOC content: Low (0.30-7.99%). EU limit value for this product (cat.A/a): 30 g/l (2010). This product contains a max of 20 g/l VOC.

**Flash Point:** Non-flammable

**Package Size:** 5 L, 2.5 L

### SURFACE PREPARATION

For best results, make sure the surfaces to be painted are sound, clean and dry. Remove any loose or flaking material, and repair damaged areas. On the surface, deep level differences should be treated with repair mortars, and slight level differences should be treated with wall putty and sanded.

Glossy surfaces should be sanded down to provide a key.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry.

If there is organic growth like mould and algae on the surface, disinfection with biological solutions should be done after mechanical cleaning.

**Priming:** WRX Trade Primer should be applied to old painted or unpainted surfaces to ensure the adhesion of free micronised powders on the prepared surfaces, to increase adherence, reduce the absorbency of the surfaces, facilitate the contrasting colour transitions, and eliminate the texture difference on the repaired surfaces.

If the surface to be painted has stains that cannot be removed by cleaning and will cause staining or bleeding after priming and painting, this area should be primed with a stain-covering primer after cleaning.

It is necessary to wait at least 6 hours for the primer to dry before applying the final coat.

## APPLICATION

Stir well before and during use. Suitable for application by brush, medium/micro fibre pile roller, conventional or airless spray. Two coats are recommended. An extra coat may be required to cover an existing darker colour. Also, specific colours may need an additional coat to cover completely.

For best results, load the brush or roller generously. Apply paint evenly and avoid overspreading. Especially with darker colours, take care to spread the paint evenly and not to over-thin.

If thinned, the paint used for cutting in and rolling should be in the same ratio. Cut in one wall at a time, then roll immediately afterwards, not allowing the cutting-in to dry before rolling.

For airless application, Pressure: 120-140 bar, Nozzle angle: 50°, Nozzle size (inch):0.015”.

**Thinning:** Thin with clean water by volume;

Brush or roller: 10%

Conventional Spray: 20 – 30%

Airless Spray: 10%

**Cleaning:** All equipment used can be cleaned with warm water and soap. Remove as much paint as possible from brushes and rollers before cleaning.

## STORAGE

Store and move in dry conditions in a secure upright position. Protect from direct sunlight, frost and extreme temperatures.

## CONSIDERATIONS

- ❖ Stir until homogeneous before use.
- ❖ Thin the amount of paint you will use.
- ❖ Apply when the air and surface temperature is above +8°C, and the relative humidity is below 80%.
- ❖ Do not apply in damp or humid conditions and very breezy environments.
- ❖ After use, replace the lid firmly.
- ❖ Use the opened product within one month.
- ❖ Apply all products in accordance with the BS 6150 Code of practice for the painting of buildings.
- ❖ Wear a suitable dust mask if dry sanding. Avoid the inhalation of dust.
- ❖ Special precautions should be taken during surface preparation of pre-1960s paint surfaces as they may contain harmful lead.

## HEALTH & SAFETY INFORMATION

- ❖ Keep out of reach of children.
- ❖ Do not get in eyes, on skin, or on clothing.
- ❖ Do not eat, drink or smoke when using this product.
- ❖ IF ON SKIN: Wash with plenty of soap and water.
- ❖ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- ❖ Dispose of contents/container through licensed companies.
- ❖ Contains mixture of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (Cas No:55965-84-9) and 2-octyl-2H-isothiazol-3-one (Cas No: 26530-20-1). May produce an allergic reaction.

This technical data sheet is based on general conditions. Please get in touch with the technical service department for detailed information, [support@wrxtrade.co.uk](mailto:support@wrxtrade.co.uk) Otherwise, our company does not accept responsibility. For more help & advice, visit us at [wrxtrade.co.uk](http://wrxtrade.co.uk).