

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : CHAIN SPRAY  
Product code : AE00A118  
Type of product : Aerosols

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

AKKIM YAPI KIMYASALLARI SANAYI VE TICARET A.S

E-mail address of competent person responsible for the SDS : [nilufer.ergin@akkim.net](mailto:nilufer.ergin@akkim.net)

#### 1.4. Emergency telephone number

Emergency number : +902127711371

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Skin corrosion/irritation, Category 2 H315  
Reproductive toxicity, Category 2 H361  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Specific target organ toxicity — Repeated exposure, Category 2 H373  
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) : Danger

Hazardous ingredients : n-hexane; toluene

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H361 - Suspected of damaging fertility or the unborn child. H373 - May cause damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe dust, fume, gas, mist, spray, vapours. P280 - Wear protective clothing, eye protection, face protection, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 - IF exposed or concerned: Get medical advice. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F, 50 °C. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Extra phrases	: For professional users only.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	30 - 40	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (Note K)(Note S)(Note U)	(CAS-No.) 68476-85-7 (EC-No.) 270-704-2 (EC Index-No.) 649-202-00-6	30 - 40	Flam. Gas 1, H220 Press. Gas
Lubricating oils; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] (Note L)	(CAS-No.) 74869-22-0 (EC-No.) 278-012-2 (EC Index-No.) 649-484-00-0	10 - 20	Not classified
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	1 - 5	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	( 5 =<C <= 100) STOT RE 2, H373

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

Note K : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Note S : This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

CHAIN SPRAY	
<b>EU - Occupational Exposure Limits</b>	
Local name	Toluene
IOELV TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
<b>Austria - Occupational Exposure Limits</b>	
Local name	Toluol
MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
MAK (ppm)	50 ppm
MAK Short time value (mg/m <sup>3</sup> )	380 mg/m <sup>3</sup>
MAK Short time value (ppm)	100 ppm
Remark (AT)	H
Regulatory reference	BGBI. II Nr. 186/2015
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Toluène # Toleuen
Limit value (mg/m <sup>3</sup> )	77 mg/m <sup>3</sup>
Limit value (ppm)	20 ppm
Short time value (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Short time value (ppm)	100 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Толуен
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
<b>Bulgaria - Biological limit values</b>	
Local name	Толуен
Bulgaria - BLV	1.6 mmol/mmol Creatinine Биомаркер за експозиция/биомаркер за ефект: хипурова киселина - Биологична среда: урина - Време на пробовземане: В края на експозицията или в края на работната смяна - Специфични ефекти: Няма
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.73 от 4 септември 2018 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Toluen
GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
GVI (granična vrijednost izloženosti) (ppm)	50 ppm
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
<b>Croatia - Biological limit values</b>	
Local name	Toluen
Croatia - BLV	10.85 µmol/l Karakteristični pokazatelj: toluen - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 1 mg/l Karakteristični pokazatelj: toluen - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 0.83 µmol/l Karakteristični pokazatelj: toluen - Biološki uzorak: krajnje izdahnuti zrak - Vrijeme uzorkovanja: za vrijeme izloženosti 20 ppm Karakteristični pokazatelj: toluen - Biološki uzorak: krajnje izdahnuti zrak - Vrijeme uzorkovanja: za vrijeme izloženosti 1.58 mol/mol Creatinine Karakteristični pokazatelj: hipurna kiselina - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene - Napomena: hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz 2.5 g/g creatinine Karakteristični pokazatelj: hipurna kiselina - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene - Napomena: hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz 1.05 mmol/mol Creatinine Karakteristični pokazatelj: o-krezol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 1 mg/g creatinine Karakteristični pokazatelj: o-krezol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Toluen (Methylbenzen)
Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Expoziční limity (PEL) (ppm)	53 ppm
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (ppm)	130 ppm
Remark (CZ)	D (při expozici se významně uplatňuje pronikání látky kůží), I (dráždí sliznice (oči, dýchací cesty) resp. Kůži)
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (zpracovány změny č. 246/2018 Sb.)
<b>Czech Republic - Biological limit values</b>	
Local name	Toluen (Methylbenzen)

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
Czech Republic - BLV	1.5 mg/g creatinine Ukazatel: o-Kresol (po hydrolyze) - Biološki uzorak: moči - Doba odběru: konec směny 1.6 µmol/mmol Creatinine Ukazatel: o-Kresol (po hydrolyze) - Biološki uzorak: moči - Doba odběru: konec směny 1600 mg/g creatinine Ukazatel: Hippurová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 1000 µmol/mmol Creatinine Ukazatel: Hippurová kyselina - Biološki uzorak: moči - Doba odběru: konec směny
Remark (BEI - CZ)	Je-li hodnota při nálezu kyseliny hippurové vyšší než 1600 mg/g, avšak nepřesahuje 2 500 mg/g kreatininu, použije se ke zpřesnění expozice toluenu biologický expoziční test podle ukazatele o-Kresol. Je-li hodnota při nálezu kyseliny hippurové vyšší než 2500 mg/g, považuje se za hodnotu prokazující, že jde o pracovní expozici toluenu, jehož hodnota PEL je překračována a biologický expoziční test podle ukazatele o-Kresol se již neprovádí.
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Toluen (Methylbenzen; Phenylmethan)
Grænseværdie (langvarig) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Grænseværdie (langvarig) (ppm)	25 ppm
Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)
Regulatory reference	BEK nr 655 af 31/05/2018
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Tolueen (metüülbenseen)
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Remark (ET)	A (Naha kaudu kergesti absorbeeruvad ained)
Regulatory reference	Vabariigi Valitsuse 18. septembri 2001. a määruse nr 293 (RT I, 30.11.2011, 5)
<b>Finland - Occupational Exposure Limits</b>	
Local name	Tolueeni
HTP-arvo (8h) (mg/m <sup>3</sup> )	81 mg/m <sup>3</sup>
HTP-arvo (8h) (ppm)	25 ppm
HTP-arvo (15 min)	380 mg/m <sup>3</sup>
HTP-arvo (15 min) (ppm)	100 ppm
Huomautus (FI)	iho, melu
Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveystieteiden ministeriö)
<b>Finland - Biological limit values</b>	
Local name	Tolueeni
Finland - BLV	500 nmol/l Parametri: Veren tolueeni - Näytteenottoajankohta: Työpäivän jälkeinen aamu
Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveystieteiden ministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Toluène
VME (mg/m <sup>3</sup> )	76.8 mg/m <sup>3</sup>
VME (ppm)	20 ppm
VLE (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
VLE (ppm)	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
TRGS 900 Local name	Toluol
Occupational exposure limit value (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
Occupational exposure limit value (ppm)	50 ppm
Limitation of exposure peaks	4(II)
TRGS 900 Remark	DFG;EU;H;Y
TRGS 900 Regulatory reference	TRGS900
<b>Germany - Biological limit values (TRGS 903)</b>	
TRGS 903 Local name	Toluol
TRGS 903 Biological limit value	600 µg/l Parameter: Toluol - Untersuchungsmaterial: B = Vollblut - Probenahmezeitpunkt: g) unmittelbar nach Exposition - Festlegung/Begründung: 11/2017 DFG 1.5 mg/l Parameter: o-Kresol (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2017 DFG 75 µg/l Parameter: Toluol - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2018 DFG
TRGS 903 Regulatory reference	TRGS 903
<b>Gibraltar - Occupational Exposure Limits</b>	
Name of agent	Toluene
Eight hours mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
Eight hours ppm	50 ppm
Short-term mg/m <sup>3</sup>	384 mg/m <sup>3</sup>
Short-term ppm	100 ppm
Notation	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Τολουόλιο
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Regulatory reference	Π.Δ. 162/2007
<b>Hungary - Occupational Exposure Limits</b>	
Local name	TOLUOL
AK-érték	190 mg/m <sup>3</sup>
CK-érték	380 mg/m <sup>3</sup>
<b>Hungary - Biological limit values</b>	
Local name	Toluol
Regulatory reference	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet a munkahelyek kémiai biztonságáról

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Toluene
OEL (8 hours ref) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	50 ppm
OEL (15 min ref) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL (15 min ref) (ppm)	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
<b>Italy - Occupational Exposure Limits</b>	
Local name	Toluene
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
Notes	pelle
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Toluols (metilbenzols)
OEL TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
OEL TWA (ppm)	14 ppm
OEL STEL (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
OEL STEL (ppm)	40 ppm
Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325 (Grozījumi Ministru kabineta 2015.gada 7.aprīlī noteikumiem Nr.163)
<b>Latvia - Biological limit values</b>	
Local name	Toluolam
Latvia - BLV	1.6 g/g creatinine Urīnā maiņas beigās nosaka hipurskābi 0.05 mg/l Toluolu asinīs
Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325 (MK 10.07.2018)
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Toluenas
IPRV (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
IPRV (ppm)	50 ppm
TPRV (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
TPRV (ppm)	100 ppm
Remark (LT)	R (reprodukcijai toksiškas poveikis); O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Luxembourg - Occupational Exposure Limits</b>	
Local name	Toluène
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm



# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
Regulatory reference	Mémorial A N° 684 de 2018
<b>Malta - Occupational Exposure Limits</b>	
Local name	Toluene
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Regulatory reference	S.L.424.24 (L.N.57 of 2018)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Tolueen
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
Regulatory reference	Arbeidsomstandighedenregeling 2018
<b>Poland - Occupational Exposure Limits</b>	
Local name	Toluen
NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
NDSch (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Remark (PL)	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową)
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Tolueno
OEL TWA (ppm)	20 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Portugal - Biological limit values</b>	
Local name	Tolueno
Portugal (BEI)	0.02 mg/l Parâmetro: Tolueno - Meio: sangue - Momento da amostragem: Antes do último turno da semana de trabalho 0.03 mg/l Parâmetro: Tolueno - Meio: urina - Momento da amostragem: Fim do turno 0.3 mg/g creatinine Parâmetro: o-Cresol - Meio: urina - Momento da amostragem: Fim do turno - Notação: Vb (Valor basal), Com hidrólise
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	Toluen
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Regulatory reference	Hotărârea nr. 584/2018
<b>Romania - Biological limit values</b>	
Local name	Toluen
Romania - BLV	2 g/l Indicador biologic: Acid hipuric - Material biologic: urină - Momentul recoltării: sfârșit schimb 3 mg/l Indicador biologic: o-cresol - Material biologic: urină - Momentul recoltării: sfârșit schimb

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
Regulatory reference	Hotărârea nr. 584/2018
<b>Serbia - Occupational Exposure Limits</b>	
Local name	толуен
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Notes	EU** – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2006/15/ЕЗ (друга листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09 и 117/17)
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Toluén
NPHV (priemerná) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
NPHV (priemerná) (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Upozornenie (SK)	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
<b>Slovakia - Biological limit values</b>	
Local name	Toluén
Slovakia - BLV	600 µg/l Zisťovaný faktor: Toluén - Vyšetovaný materiál: krv - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny 1.5 mg/l Zisťovaný faktor: O-krezol - Vyšetovaný materiál: moč - Čas odberu vzorky: c) pri dlhodobej expozícii; po viacerých pracovných zmenách, b) koniec expozície alebo pracovnej zmeny 2401 mg/l Zisťovaný faktor: Kyselina hippurová - Vyšetovaný materiál: moč - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny 1600 mg/g creatinine Zisťovaný faktor: Kyselina hippurová - Vyšetovaný materiál: moč - Čas odberu vzorky: b) koniec expozície alebo pracovnej zmeny
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (Zmena: 471/2011 Z.z.)
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	toluen
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Remark (SI)	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
<b>Slovenia - Biological limit values</b>	
Local name	toluen
Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
<b>Spain - Occupational Exposure Limits</b>	
Local name	Tolueno

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
VLA-ED (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
VLA-ED (ppm)	50 ppm
VLA-EC (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
VLA-EC (ppm)	100 ppm
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Spain - Biological limit values</b>	
Local name	Tolueno
Spain - BLV	0.6 mg/l Parámetro: o-Cresol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB) 0.05 mg/l Parámetro: Tolueno - Medio: Sangre - Momento de muestreo: Principio de la última jornada de la semana laboral 0.08 mg/l Parámetro: Tolueno - Medio: orina - Momento de muestreo: Final de la jornada laboral
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Toluen
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
nivågränsvärde (NVG) (ppm)	50 ppm
kortidsvärde (KTV) (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
kortidsvärde (KTV) (ppm)	100 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Toluene
WEL TWA (mg/m <sup>3</sup> )	191 mg/m <sup>3</sup>
WEL TWA (ppm)	50 ppm
WEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
WEL STEL (ppm)	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Tólúen (fenýlmetan, metýlbensen)
OEL (8 hours ref) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	25 ppm
OEL (15 min ref) (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
OEL (15 min ref) (ppm)	50 ppm
Notes (IS)	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Toluen
Grenseverdier (AN) (mg/m <sup>3</sup> )	94 mg/m <sup>3</sup>
Grenseverdier (AN) (ppm)	25 ppm

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

<b>CHAIN SPRAY</b>	
Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); E (EU har en veiledende grenseverdi for stoffet)
Regulatory reference	FOR-2018-08-21-1255
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Toluène / Toluol
MAK (mg/m <sup>3</sup> )	190 mg/m <sup>3</sup>
MAK (ppm)	50 ppm
KZGW (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
KZGW (ppm)	200 ppm
Critical toxicity	Vue, SNC / Sehen, ZNS
Notation	R, R <sub>2D</sub> , R <sub>2F</sub> , S <sub>Sc</sub> , O <sup>B</sup> , B / H, R <sub>2D</sub> , R <sub>2F</sub> , S <sub>Sc</sub> , O <sup>L</sup> , B
Remark	INRS, HSE, NIOSH, DFG
Regulatory reference	www.suva.ch, 01.07.2019
<b>Turkey - Occupational Exposure Limits</b>	
Local name	Toluen
OEL TWA (mg/m <sup>3</sup> )	192 mg/m <sup>3</sup>
OEL TWA (ppm)	50 ppm
OEL STEL (mg/m <sup>3</sup> )	384 mg/m <sup>3</sup>
OEL STEL (ppm)	100 ppm
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Toluene
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	TLV® Basis: Visual impair; female repro; pregnancy loss. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2019

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

EN 374. Protective gloves

#### Eye protection:

Chemical goggles or face shield. EN 166. Safety glasses

#### Respiratory protection:

EN 14387. [In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid under pressure.
Colour	: Brown.
Odour	: Hydrocarbons.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.801 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified



# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

### 14.5. Environmental hazards

Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
-------------------------------------	---	-------------------------------------	-------------------------------------	-------------------------------------

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

#### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2

# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
48.	toluene	Toluene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WKG) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)

SZW-lijst van kankerverwekkende stoffen : Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).], Lubricating oils; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from solvent extraction and dewaxing processes. It consists predominantly of saturated hydrocarbons having carbon numbers in the range C15 through C50.] are listed

SZW-lijst van mutagene stoffen : Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : n-hexane is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : toluene is listed

##### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out



# CHAIN SPRAY

## Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 25.12.2019

Version: 0.0

### SECTION 16: Other information

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

AKKIM SDS EU

*DISCLAIMER OF LIABILITY* The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable