

Technical Information

Product name : WRX Contact Cleaner

Supplier / Producer : AKCALI UK LTD.

26 St Cross Street, EC1

London - UK

Telephone number +44 2036082616

Product description

High quality spray to clean electrical contacts.

Applications

Switches
Batteries
Contact Points
Printed Circuit Board Switches
Multiple Sockets

Product characteristics

Powerful jetspray
High dissolving properties Leaves no residue
Non-conductive
Non-corrosive
360° valve

Physical and Chemical Characteristics

Contents : 400 ml

Basis : Aliphatic Hydrocarbons

with alcohol

Propellant : Carbondioxide

Colour : Transparent
Scent : Characteristic
Relative density at 20°C : 0,73 g/ml
Yield : 3,8 g/sec
Refractive Index at 20°C : 1,370

Vapour pressure at 20°C : 5,5 to 6,5 bar

VOC Content : Approximately 97% w/w

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.

Best processing temperature 5 to 30°C.

Before use, shake the aerosol.

Switch off electrical installations before treatment.

Spray the parts to be treated until the contamination has disappeared.

Contaminated contact cleaner should be regarded as chemical waste.

Only switch on the electrical installation after evaporation of the solvent (minimum of 15 minutes).





