

<b>Product name</b>	:	<b>WRX Penetrating Oil</b>
<b>Supplier / Producer</b>	:	<b>AKCALI UK LTD. 26 St Cross Street, EC1 London – UK</b>
<b>Telephone number</b>		<b>+44 2036082616</b>

### Product description

High quality effective tool to loosen rusted parts.

### Applications

Fastenings, Tools  
Screwed connections, Rails  
Gear wheels, Chains Locks, Garden tools  
Fasteners (screws, bolts and nuts), Reels

### Product characteristics

Good penetrating properties  
Contains graphite and MoS<sub>2</sub>  
Corrosion preventive  
Powerful jetspray  
360° valve  
Moisture repellent

### Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Mineral Oil and graphite and MoS <sub>2</sub>
VOC-content	:	Approximately 70% w/w
Colour	:	Graphite / Black
Scent	:	Characteristic
Relative density at 20°C	:	0,86 g/ml
Yield	:	2,33 g/sec
Vapour pressure at 20°C	:	to 4 bar

### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.

Apply penetrating oil and allow it to take effect.

