

Product name	:	WRX White Grease
Supplier / Producer	:	AKCALI UK LTD. 26 St Cross Street, EC1 London – UK
Telephone number		+44 2036082616

Product description

High quality spray grease to lubricate mechanical parts of metal or plastic.

Applications

Metal to metal connections, Roller bearings,
Door hinges, Ball bearings, Metal to plastic connections
Springs, Stabilization rubbers, Sliding bearings
Shock absorbers, Worm wheels

Product characteristics

Outstanding mechanical and thermal stability
Excellent adhesion
Prevents wear and sticking
High viscosity
Resistant to weather influences
Resistant to weak acids and bases
Excellent corrosion prevention Water-repellent
Contains PTFE (polytetrafluorethen)
Directed jetspray

Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Mineral Oil with EP Grease
VOC-content	:	Approximately 71% w/w
Colour	:	Beige
Scent	:	Characteristic
Appearance	:	Grease
Relative density at 20°C	:	0,76 g/ml
Yield	:	1,51 g/sec
Vapour pressure at 20°C	:	to 4 bar
Ball EP-test (ASTM D 2596)	:	N
Ball Wear-test (ASTM D 2266)	:	< 0,4 mm
Temperature resistant	:	-30°C tot +160°C
pH-value	:	Neutral

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply the white grease in a thin layer.
Optimum lubrication is obtained after evaporation of the solvent.

