

WRX TRADE MULTI-GRIP ALL SURFACE PAINT

Product Data Sheet

Product Number: 03.611

Issued: 11/2025

Revision: 00

DESCRIPTION

A high-quality, water-based, suitable for tricky surfaces, pure acrylic top-coat paint with a semi-matt finish.

USAGE AREA

Suitable for both interior and exterior use on a wide range of surfaces including wood, metal, plaster, brick, tile, porcelain, marble, ceramic, doors, windows, furniture, coffee tables, white goods, cabinets, and vases.

PROPERTIES

Thanks to its advanced formulation, it offers excellent adhesion even on challenging surfaces where conventional paints typically struggle without the need for primer or undercoat. It provides outstanding coverage and durability, resisting water, household chemicals, detergents, and physical impacts. Formulated with Stain Repellent Technology, it allows for easy cleaning of common household stains and dirt. It forms a tough, protective film with high scrub resistance (Class 1, ISO 11998). Low odour and free from heavy metals harmful to human health, it complies with EN 71-3 safety standards, making it suitable for use on children's toys and furniture during renovations.

PRODUCT INFORMATION

Finish	: Semi matt
Colour Range	: Card colours
Composition	:
Solvent	: Water
Binder	: Acrylic polymer
Pigment	: Titanium dioxide, coloured pigments, extenders
Volume Solids	: 36 ± 2%, white. Other colours will vary.
Coverage	: WRX Trade Multi-Grip All Surface Paint will cover up to 16 m ² per litre, depending on the surface conditions.
Wet Film Thickness	: 62 micrometres at 16 m ² per litre
Dry Film Thickness	: 22 micrometres at 16 m ² per litre
Drying Time	: Touch dry in half an hour under normal conditions. Allow 2-4 hours between coats. High humidity can extend the drying time. Fully cured after 28 days.
VOC Content:	: VOC content: Low (0.30-7.99%). EU limit value for this product (cat.A/i): 140 g/l (2010). This product contains a max of 35 g/l VOC.
Flash Point	: Non-flammable
Package Size	: 2.5 L, 1 L.

SURFACE PREPARATION

For best results, all surfaces must be sound, clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied like grease or dust. Remove any loose or flaking material, and repair damaged areas. On the surface, deep level differences should be treated with repair mortars, and slight level differences should be treated with wall putty and sanded.

Chalky, weathered or highly porous surfaces should be treated with a clear surface stabiliser.

If there is organic growth like mould and algae on the surface, disinfection with biological solutions should be done after mechanical cleaning.

Bare metal surfaces must be degreased, and any rust-prone areas should be primed with an anti-rust primer.

Wooden surfaces should be sanded along the grain, thoroughly cleaned to remove dust and resin, and bare wood should be treated with a wood preservative.

On plastic or other low-adhesion surfaces, carry out an adhesion test on a small, inconspicuous area before

full application.

Smooth, glossy surfaces should be lightly abraded to ensure proper adhesion.

If the surface to be painted has stains that cannot be removed by cleaning and will cause staining or bleeding after priming and painting, this area should be primed with a stain-covering primer after cleaning.

APPLICATION

Stir well before and during use. Suitable for application with a high-quality synthetic brush, short-pile microfibre roller, or spray. For optimal results, load the brush or roller generously and apply the paint evenly, avoiding overspreading. Two coats are recommended for full coverage. Additional coats may be required when painting over darker colours.

For airless application, Pressure: 100-120 bar, Nozzle size (inch):0.013"-0.015".

Thinning: Ready to use. If required, it can be thinned up to 10% with clean water.

Cleaning: All equipment used can be cleaned with warm water or soapy water. Remove as much paint as possible from brushes and rollers before cleaning. Do not empty paint into drains or watercourses.

STORAGE

Store and transport in dry conditions in a secure upright position. Protect from direct sunlight, frost and extreme temperatures.

CONSIDERATIONS

- ❖ Stir until homogeneous before use.
- ❖ Thin the amount of paint you will use.
- ❖ Apply when the air and surface temperature is above +8°C, and the relative humidity is below 80%.
- ❖ Do not apply in damp or humid conditions, in rainy weather, in extremely windy environments.
- ❖ After use, replace the lid firmly.
- ❖ Use the opened product within one month.
- ❖ Apply all products in accordance with the BS 6150 Code of practice for the painting of buildings.

HEALTH & SAFETY INFORMATION

- ❖ Wear a suitable dust mask if dry sanding. Avoid the inhalation of dust.
- ❖ Special precautions should be taken during surface preparation of pre-1960s paint surfaces as they may contain harmful lead.
- ❖ Keep out of reach of children.
- ❖ Do not get in eyes, on skin, or on clothing.
- ❖ Do not eat, drink or smoke when using this product.
- ❖ IF ON SKIN: Wash with plenty of soap and water.
- ❖ IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- ❖ Dispose of contents/container through licensed companies.
- ❖ Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Cas No: 55965-84-9) and 1,2-benzisothiazol-3(2H)-one (Cas No: 2634-33-5). May produce an allergic reaction.
- ❖ Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- ❖ Please refer to the Safety Data Sheet of product for safety, health and environmental Information.

This technical data sheet is based on general conditions. Please get in touch with the technical service department for detailed information, support@wrxtrade.co.uk Otherwise, our company does not accept responsibility. For more help & advice, visit us at wrxtrade.co.uk.